

XCFR8.E244285 - TERMINAL BLOCKS CERTIFIED FOR CANADA - COMPONENT

Terminal Blocks Certified for Canada - Component

See General Information for Terminal Blocks Certified for Canada - Component

IMO PRECISION CONTROLS LTD
The Interchange Frobisher Way
Hatfield, AL10 9TG UNITED KINGDOM

E244285

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
EPSC 1.5-4	22-12 STR	Cu	—	600	20	B,C,D	2(105)
EPSC 1.5-4GREEN	22-12 STR	Cu	—	—	—	B,C,D	2(105)
ER 2.5	26-12	Cu	0.4	600	20	B,C	2(105)
ER 2.5P	26-12SOL/STR	Cu	0.4	600	20	B, C,D	2(105)
ER 2.5-T15	26-12	Cu	0.4	300	20	B,C	2(105)
ER 4	26-10	Cu	0.5	300	30	B,C	2(105)
				600		D	
ER 4P	26-10SOL/STR	Cu	0.5	600	30	B, C,D	2(105)
ER 4-T15	24-10	Cu	0.5	300	30	B,C	2(105)
ER 6	26-8	Cu	0.8	300	50	B,C	2(105)
				600		D	
ER 10	16-6	Cu	1.2	300	65	B,C	2(105)
ER 16	12-4	Cu	1.2	600	85	B,C	2(105)
ER 16P	12-4 STR 12-10 SOL	Cu	2.0	600	80	B,C	2(105)
ER 25P	12-2 STR 12-10 SOL	Cu	4.0	600	100	B, C, D	2(105)
ER 35	10 SOL 8- 2 STR	Cu	2.5	600	115	B,C	2(105)
ER 35P	12-2 STR 12-10 SOL	Cu	2.5	600	115	B,C	2(105)
ER 50	6-1/0 STR	Cu	6.0	600	150	B, C,D	2(105)
ER 70	6-2/0	Cu	6	600	175	B,C	2(105)
ER 95	2-4/0	Cu	15.0	600	230	B,C	2(105)
ER 150	2 AWG-300 kcmil	Cu	18.0	600	270	B,C	2(105)
ER 240	2/0 AWG-500 kcmil	Cu	20.0	600	370	B,C	2(105)
ERD 2.5	26-12	Cu	0.4	300	20	B,C	2(85)
ERD 2.5V	26-12	Cu	0.4	300	20	B,C	2(85)
ERD 2.5D	26-12	Cu	0.4	300	20	B,C	2(85)
ERD 2.5LD	26-12	Cu	0.4	300	20	B,C	2(85)
ERD 4	26-10	Cu	0.5	300	30	B,C,D	2(85)
ERD 4V	26-10	Cu	0.5	300	30	B,C,D	2(85)
ERD 4D	26-10	Cu	0.5	300	30	B,C,D	2(85)
ERD 4LD	26-10	Cu	0.5	300	30	B,C,D	2(85)
ERD4F	24-10	Cu	0.5	300	6.3-30	B,C	2(105)
ERF 4	22-8	Cu	0.8	600	6.3	B,C	2(85)
ERF3 LD (1)	26-10	Cu	0.5	600	10	B,C,D	2(105)
ERF 3MLD (1)	26-10	Cu	0.5	600	10	B,C,D	2(105)
ERPE 2.5/4	26-10	Cu	0.5	—	—	—	2(105)
ERPE 2.5P	26-12 SOL/STR	Cu	0.5	—	—	B, C,D	2(105)

ERPE 4P	26-10SOL/STR	Cu	0.5	—	—	B, C, D	2(105)
ERPE 4-T15 (2)	24-10	Cu	0.5	—	—	B, C	2(105)
ERPE 6/10	16-8	Cu	1.2	—	—	—	2(105)
ERPE 16P	12-4 STR 12-10 SOL	Cu	2.0	600	—	B, C	2(105)
ERPE 35P	12-2 STR 12-10 SOL	Cu	2.5	600	—	B, C	2(105)
ERPE 50	6-1/0 STR	Cu	10	600	—	B, C, D	2(105)
ERPE 2.5-T15	26-12 STR	Cu	0.7	—	—	B, C, D	2(105)
ERTD 3	26-10	Cu	0.5	600	10	B, C, D	2(105)
ERTD 4	26-10	Cu	0.5	600	10	B, C, D	2(105)
ERF 3M	26-10	Cu	0.5	600	10	B, C, D	2(105)
ERT 2E	24-12	Cu	0.4	300	24	B, C, D	2(105)
ERT 3 (2)	24-12	Cu	0.4	300	24	B, C, D	2(105)
ERT 3E				600			
SC 2.5	22-12	Cu	2	—	600	20	B, C
SC 4	22-10 stranded	Cu	2	—	600	26	B, C
SC 6	22-8	Cu	2	—	600	35	B, C
SC 10	20-6	Cu	2	—	600	50	B, C
SCB 2.5	22-12 STR	Cu	—	600	20	B, C, D	2(105)
SCBC 2.5	22-12 STR	Cu	—	600	20	B, C, D	2(105)
SCD 2.5	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCD 2.5C	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCD 2.5CLD	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCD 2.5E	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCD 2.5PE (1)	22-12 stranded	Cu	—	—	—	B, C	2(85)
SCD 4	22-10	Cu	2	—	600	20	B, C
SCF 3	22-10	Cu	2	—	600	10	B, C
SCF 4D	22-10	Cu	—	600	10	B, C	2(85)
SCPE 2.5 (1)	22-12	Cu	2	—	—	—	B, C
SCPE 4 (1)	22-10 stranded	Cu	2	—	—	—	B, C
SCPE 6 (1)	22-8	Cu	2	—	—	—	B, C
SCPE 10 (1)	20-6	Cu	2	—	—	—	B, C
SCS 2.5	22-12 stranded	Cu	—	300	10	B, C	2(85)
SCS 2.5E	22-12 stranded	Cu	—	300	10	B, C	2(85)
SCS 2.5L	22-12 stranded	Cu	—	300	10	B, C	2(85)
SCS 2.5EL	22-12 stranded	Cu	—	300	10	B, C	2(85)
SCT 2E (1)	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCT 3	22-12	Cu	2	—	600	26	B, C
SCT 3E	22-12 stranded	Cu	—	600	20	B, C	2(85)
SCTD 4	22-12 stranded	Cu	—	600	10	B, C	2(85)
ER35PV	12-2 STR 12-10 SOL	Cu	2.5	1000	115	E	2(105)
ER50	6-1/0 STR	Cu	6.0	600	150	B, C, D	2(105)
ER50V	6-1/0 STR	Cu	8.0	1000	150	E	2(105)
ER70P	6-2/0	Cu	10	1000	175	E	2(105)
ER70V	6-2/0	Cu	10	1000	175	E	2(105)
ER70PV	6-2/0	Cu	10	1000	175	E	2(105)
20.5701M/xx-E	20-16, str/sol	Cu	—	300	10	B	2(120)

					Note A	D	
ERF 4LD 110 V AC	22-8	Cu	0.8	110	6.3	B, C	2(85)
ERF 4LD 110 V DC	22-8	Cu	0.8	110	6.3	B, C	2(85)
ERF 4LD 220 V AC	22-8	Cu	0.8	220	6.3	B, C	2(85)
ERF 4LD 220 V DC	22-8	Cu	0.8	220	6.3	B, C	2(85)
ERF 4LD 24 V AC	22-8	Cu	0.8	24	6.3	B, C	2(85)
ERF 4LD 24 V DC	22-8	Cu	0.8	24	6.3	B, C	2(85)
ERF 4LD 48 V AC	22-8	Cu	0.8	48	6.3	B, C	2(85)
ERF 4LD 48 V DC	22-8	Cu	0.8	48	6.3	B, C	2(85)
ERF 4	22-8	Cu	0.8	600	6.3	B, C	2(85)
ERPEY 10	16-6 SOL/STR	Cu	1.8	300	—	B, C	2(105)
				600		D	
ER 2.5DD	26-12	Cu	0.8	600	20	B, C	2(105)
ERDTPE 2.5	26-12	Cu	0.8	—	—	B, C	2(105)
ERPEY 2.5/4	26-10 SOL/STR	Cu	0.8	300	—	B, C	2(105)
				600		D	
ERTD 4A	26-10 SOL/STR	Cu	0.8	300	16	B, C	2(105)
				600		D	2(105)
ERD 4FLD 110 V AC/DC	24-10	Cu	0.5	110 Fuse bar 300 Main bar	6.3 Fuse bar 30 Main bar	B, C	2(105)
ERD 4FLD 220 V AC/DC	24-10	Cu	0.5	220 Fuse bar 300 Main bar	6.3 Fuse bar 30 Main bar	B, C	2(105)
ERD 4FLD 24 V AC/DC	24-10	Cu	0.5	24 Fuse bar 300 Main bar	6.3 Fuse bar 30 Main bar	B, C	2(105)
ERD 4FLD 48 V AC/DC	24-10	Cu	0.5	48 Fuse bar 300 Main bar	6.3 Fuse bar 30 Main bar	B, C	2(105)
ERPEY 6	26-8 SOL/STR	Cu	1.2	300	—	B, C	2(105)
			1.2	600		D	
ERT 3S	24-12	Cu	0.5	300	20	B, C, D	2(105)
ERT 3SLD	24-12	Cu	0.5	300	20	B, C, D	2(105)
PF 1.5	22-14	Cu	—	600	15	B, C, D	2(105), 4
PFPE 1.5P	22-14	Cu	—	600	—	B, C, D	2(105), 4
PFPE 10P	20-6	Cu	—	600	—	B, C, D	2(105), 4
PFPE 16P	4-20	Cu	—	600	—	B, C	2(105)
PFT 2E(3)	22-12	Cu	—	300	20	B, C	2(105), 4
				600		D	
PFT 3	22-12	Cu	—	300	20	B, C	2(105), 4
				600		D	
PFT 3E(4)	22-12	Cu	—	300	20	B, C	2(105), 4
				600		D	
PFF 3LD 220 V AC	22-10	Cu	—	150	10	C	2(105)
				220		B,D	
PFF 3LD 24 V DC	22-10	Cu	—	24	10	B,C,D	2(105)
PFF 4LD520 220 V AC	22-10	Cu	—	150	10	C	2(105)
				220		B,D	
PFF 4LD520 24 V DC	22-10	Cu	—	24	10	B,C,D	2(105)
ERWT 1N	20-8 SOL/STR	Cu	1.2	300	50	B, C	2(105)
						D	
ERWT 3N	20-8 SOL/STR	Cu	0.8	300	43	B, C	2(105)
						D	
SCT 3S	22-12	Cu	—	300	20	B, C, D	2(105)

SCP-PT2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-PTCC2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-PTD2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-PTA2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 2.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 22D2.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 22DB2.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 212.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 22K2.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP 222.5GREY	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-FM2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-HM2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCP-HO2.5	12-28	Cu	—	300	20	B, C, D	2(120)
SCPPP2.5GREY	—	—	—	300	20	B, C, D	2(120)
SCPPE2.5P	12-28	Cu	—	300	—	B, C, D	2(120)
SCP22DLP2.5GREY	12-28	Cu	—	300	—	B, C, D	2(120)
SCP22DBPE2.5P	12-28	Cu	—	300	—	B, C, D	2(120)
SCP21PE2.5P	12-28	Cu	—	300	—	B, C, D	2(120)
SCP22PE2.5P	12-28	Cu	—	300	—	B, C, D	2(120)
SCPPPE2.5P	12-28	Cu	—		—	B, C, D	2(120),4
Note: (1) These terminal block are provided with grounding bars as part of the terminal block. These ground bars have been evaluated for their suitability as protective conductor terminal blocks.							
Note: (2) These terminal block are provided with grounding bars as part of the terminal block. These ground bars have been evaluated for their suitability as protective conductor terminal blocks.							
Note: (3) This is a three level terminal block. The lower level is used for grounding.							
Note: (4) This is a four level terminal block. The lower level is used for grounding.							

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
20.552M/XX	16-30	Cu	0.20	300	12	B	1,2,(65),4
				300	Note A	D	
20.553M/XX	16-30	Cu	0.20	300	12	B	1,2,(65),4
				300	Note A	D	
20.554M/XX	16-30	Cu	0.20	300	12	B	1,2,(65),4
				300	Note A	D	
20.510M/XX	16-sol	Cu	0.23	300	10	B	2(105),4
	18-24	Cu	0.23	300	10	B	2(105),4
20.514M/XX	18-24	Cu	0.23	300	10	B	2(105),4
	16-sol	Cu	0.23	300	10	B	2(105),4
21.558M/XX	16-30	Cu	0.20	150	12	C,D	1,2,(65),4
	16-30	Cu	0.20	300	12	B	1,2,(65),4
21.559M/XX	16-30	Cu	0.20	150	12	C,D	1,2,(65),4
	16-30	Cu	0.20	300	12	B	1,2,(65),4
21.510M/XX	18-24	Cu	0.23	300	10	B	2(105),4
	16-sol	Cu	0.23	300	10	B	2(105),4
21.514M/XX	18-24	Cu	0.23	300	10	B	2(105),4
	16-sol	Cu	0.23	300	10	B	2(105),4
21.553M/XX	16-30	Cu	0.20	150	12	C,D	1,2,(65),4

	16-30	Cu	0.20	300	12	B	1,2,(65),4
21.554M/XX	16-30	Cu	0.20	150	12	C,D	1,2,(65),4
	16-30	Cu	0.20	300	12	B	1,2,(65),4
21.556M/XX	26-16	Cu	0.19	300	10	B	2(105)
21.557M/XX	16-30	Cu	0.20	300	12	B	1,2,(65),4
	16-30	Cu	0.20	150	12	C,D	1,2,(65),4
20.251M/XX	16-14 STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
	30-16	Cu	0.5	300	13.5	B	2(105)
	SOL/STR						
				300	Note A	D	
20.351M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.350M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.355M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.700M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
20.800M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
20.783M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.793M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.751M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.752M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.753M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.352M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.353M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
20.354M/XX	22-28 (b)	Cu	0.50	300	20	B	2(105),4
				300	Note A	D	
20.502M/XX	26-14	Cu	0.50	300	8	B,C,D	1,2(105)
20.503M/XX	26-14	Cu	0.50	300	8	B,C,D	1,2(105)
20.590M/XX	26-14	Cu	0.50	300	8	B,C,D	1,2(105)
20.2250MH/XX	22-12	Cu	0.51	300	26	B	2(105),4
				300	Note A	D	
	22-12	Cu	0.51	300	20	B	2(105),4
				300	Note A	D	
20.501M/XX-SB	14-24	Cu	0.40	300	16	B,D	1,2(105),4
20.515M/XX	14-24 SOL/STR	Cu	0.40	300	16	B	1,2(105),4
				300	Note A	D	
20.105M/xx-E (h)	14-22 Sol/Str	Cu	0.25	250	16	B	2(105)
					Note A	D	
20.102M/XXSB	12-18	Cu	0.34	300	12	B	2(105),4*

				300	Note A	D	
21.251M/XX	16-14 STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
	30-16 SOL/STR	Cu	0.5	300	13.5	B	2(105)
				300	Note A	D	
21.252M/XX	26-16 SOL/STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
	16 SOL/STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
	26-18 SOL/STR	Cu	0.56	300	13.5	B,D	2(105)
				300	Note A	D	
	16-14 STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
21.351M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.350M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.700M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
21.705M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
21.783M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.793M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.751M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.752M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.753M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.352M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.353M/XX	12-24	Cu	0.50	300	20	B	1,2(105),4
				300	Note A	D	
21.750M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
21.754M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
21.755M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
21.756M/XX	26-12	Cu	0.79	300	23	B	2(105),4
				300	Note A	D	
21.501M/XX-SB	14-24 SOL/STR	Cu	0.40	300	16	B	1,2(105),4
				300	Note A	D	
20.515 M/XX	14-24 SOL/STR	Cu	0.40	300	16	B	1,2(105),4
				300	Note A	D	
21.4200M/XX	14-28 sol	Cu	—	300	14	B	2(105),4
				300	Note A	D	
21.4200MF/XX	14-28 sol	Cu	—	300	14	B	2(105),4
				300	Note A	D	
21.840M/XX	26-10	Cu	0.79	300	30	B	2(105),4
				300	Note A	D	

20.346M/XX-E (g), 20.376M/XX-E (g)	12-22 Sol/Str	Cu	3.5	300	16	B	2(65)
					Note A	D	
20.710M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
20.810M/XX	24-12 SOL/STR	Cu	0.45	300	25	B,C	2(105)
20.841M/XX	24-10	Cu	1.37	300	30	BC	2(105),4
				600	30	D	
20.356M/XX	24-12	Cu	0.50	300	10	D	1,2(105),4
20.357M/XX	24-12	Cu	0.50	300	10	D	1,2(105),4
20.2275MH/XX	22-12	Cu	0.51	300	26	B	2(105),4
				300	Note A	D	
	22-12	Cu	0.51	300	20	B	2(105),4
				300	Note A	D	
20.103M/XX	12-18	Cu	0.34	150	12	C	2(105),4*
				300	12	B	
				300	Note A	D	
21.4201M/XX	14-28 sol	Cu	—	300	14	B	2(105),4
				300	Note A	D	
21.841M/XX	24-10	Cu	1.37	300	30	B,C	2(105),4
				600	Note A	D	
20.842M/XX	26-10	Cu	0.50	300	30	B,C	2(105),4
				300	Note A	D	
	26-10	Cu	0.50	600	Note A	D	2(105),4
20.104M/XX	12-18	Cu	0.34	600	Note A	D	2(105),4*
21.843M/XX	20-6	Cu	1.76	300	65	B,C	2(105),4
	20-6	Cu	1.76	600	Note A	D	2(105),4
20.1550M/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.1550MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.1500M/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.1500MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.1510M/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.1510MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
20.155MV/XX	—	—	—	300	8	B,D	2(65)
20.155MVF/XX	—	—	—	300	8	B,D	2(65)
20.155MH/XX	—	—	—	300	8	B,D	2(65)
20.155MHF/XX	—	—	—	300	8	B,D	2(65)
20.156MV/XX	—	—	—	300	8	B,D	2(105)
20.156MVF/XX	—	—	—	300	8	B,D	2(105)
20.156MH/XX	—	—	—	300	8	B,D	2(105)
20.156MHF/XX	—	—	—	300	8	B,D	2(105)
20.157MV/XX	—	—	—	300	8	B,D	2(105)
20.157MVF/XX	—	—	—	300	8	B,D	2(105)
20.157MH/XX	—	—	—	300	8	B,D	2(105)
20.157MHF/XX	—	—	—	300	8	B,D	2(105)
20.155MH/XXHT	—	—	—	300	8	B,D	2(65)
20.155MHF/XXHT	—	—	—	300	8	B,D	2(65)
20.155MV/XXHT	—	—	—	300	8	B,D	2(65)
20.155MVF/XXHT	—	—	—	300	8	B,D	2(65)
21.1550/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4

21.1550MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
21.1500M/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
21.1500MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
21.1510M/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
21.1510MF/XX	28-14 SOL/STR	Cu	0.19	300	8	B,D	2(105),4
21.1551MF/XX	16-28	Cu	N/A	300	8	B,D	2(105),4
21.155MV/XX	—	—	—	300	8	B,D	2(105)
21.155MVF/XX	—	—	—	300	8	B,D	2(105)
21.155MH/XX	—	—	—	300	8	B,D	2(105)
21.155MHF/XX	—	—	—	300	8	B,D	2(105)
21.156MV/XX	—	—	—	300	8	B,D	2(105)
21.156MVF/XX	—	—	—	300	8	B,D	2(105)
21.156MH/XX	—	—	—	300	8	B,D	2(105)
21.156MHF/XX	—	—	—	300	8	B,D	2(105)
21.157MV/XX	—	—	—	300	8	B,D	2(105)
21.157MVF/XX	—	—	—	300	8	B,D	2(105)
21.157MH/XX	—	—	—	300	8	B,D	2(105)
21.157MHF/XX	—	—	—	300	8	B,D	2(105)
21.155MH/XXHT	—	—	—	300	8	B,D	2(65)
21.155MHF/XXHT	—	—	—	300	8	B,D	2(65)
21.155MV/XXHT	—	—	—	300	8	B,D	2(65)
21.155MVF/XXHT	—	—	—	300	8	B,D	2(65)
20.950M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.950MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.910M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.910MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.920M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.920MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.951M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	

	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.970M/XX	24-12, SOL/STR	Cu	0.49	300	15	B	2(105),3(2.5),4
				300	Note A	D	
20.970MF/XX	24-12, SOL/STR	Cu	0.49	300	15	B	2(105),3(2.5),4
				300	Note A	D	
20.955M/XX	12-28 sol	Cu	—	300	15	B	2(105),4
20.90MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MVF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.90MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.93MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.93MVF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.93MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.93MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.90MH/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MHF/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.90MV/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MVF/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MH/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.95MV/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.950M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.950MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.970M/XX	24-12, SOL/STR	Cu	0.49	300	15	B	2(105),3(2.5),4

				300	Note A	D	
21.970MF/XX	24-12, SOL/STR	Cu	0.49	300	15	B	2(105),3(2.5),4
				300	Note A	D	
21.910M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.910MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.920M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.920MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.953M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.954M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.955M/XX	28-12 sol	Cu	—	300	15	B	2(105),4
21.90MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MVF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.90MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.92MP/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.93MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.93MVF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.93MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	

21.93MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.94MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.94MVF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.94MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.94MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MS/XX	14-28 sol	Cu	—	300	14	B	2(105),4
				300	Note A	D	
21.95MSF/XX	14-28 sol	Cu	—	300	14	B	2(105),4
				300	Note A	D	
21.90MH/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MHF/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.90MV/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MVF/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MH/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.95MV/XXHT	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.960M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.960MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.961M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.961MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.962M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.962MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	

	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
20.965M/XX	28-12 sol	Cu	—	300	15	B	2(105),4
20.91MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.96MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.91MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.96MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.96MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.96MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.960M/XX	12-28, Sol	Cu	0.51	300	12	B,D	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.960MF/XX	12-28, Sol	Cu	0.51	300	12	B,D	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.961M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.961MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.962M/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.962MF/XX	12-28, Sol	Cu	0.51	300	15	B	2(105),4
				300	Note A	D	
	12-30, Str	Cu	0.51	300	15	B	2(105), 4
				300	Note A	D	
21.965M/XX	28-12 sol	Cu	—	300	15	B	2(105),4
21.91MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.96MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.91MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.96MHF/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	

21.96MV/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
21.96MH/XX	—	—	—	300	15	B	2(105)
				300	Note A	D	
20.3003M/XX	28-20, SOL	Cu		150	4	B	2(105),4
				300	4	D	
20.3004M/XX	28-20, SOL	Cu		150	4	B	2(105),4
				300	4	D	
21.3003M/XX	28-20, SOL	Cu		150	4	B	2(105),4
				300	4	D	
21.3004M/XX	28-20, SOL	Cu		150	4	B	2(105),4
				300	4	D	
21.4102M/XX	14-20	Cu	—	300	10	B,D	2(105)
21.4300M/XX	14-20	Cu	—	300	10	B,D	2(105)
21.4103M/XX	14-20	Cu	—	300	10	B,D	2(105)
20.4100M/XX	14-20	Cu	—	300	10	B,D	2(105)
20.4101M/XX	14-20	Cu	—	300	10	B,D	2(105)
20.3000M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3001M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3101M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3111M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3200M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	2(105),4
				300	Note A	D	
20.6002M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
20.6003M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
20.6004M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
20.3102M/XX	28-15, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3112M/XX	28-15, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3201M/XX	28-15, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3010M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4

				300	15	B	
				300	Note A	D	
21.3011M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3102M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3112M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3020M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
20.3021M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
20.3103M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
20.3113M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
21.3020M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
21.3021M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
21.3103M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
21.3113M/XX	28-12, SOL/STR	Cu	—	300	15	B,C	2(105),4
				600	Note A	D	
21.3000M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3001M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3101M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.3111M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B	
				300	Note A	D	
21.6002M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
21.6003M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
21.6004M/XX	28-12, SOL/STR	Cu	—	150	10	C	2(105),4
				300	10	B,D	
20.4400M/XX	14-20	Cu	—	300	10	B,D	2(105)
				150	10	C	2(105)
20.4104M/XX	14-20	Cu	—	300	10	B,D	2(105)

				150	10	C	2(105)
20.3010M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
20.3011M/XX	28-12, SOL/STR	Cu	—	150	15	C	2(105),4
				300	15	B	
				300	Note A	D	
21.250M/XX	16-14 STR	Cu	0.8	300	13.5	B	2(105)
				300	Note A	D	
	30-16 SOL/STR	Cu	0.5	300	13.5	B	2(105)
				300	Note A	D	
21.956MV/xx(+)	24-12	Cu	—	300	Note A	D	2(105),4
21.95MVT/xx (+)	28-16, two wires	Cu	0.56	300	15	B	2(105)
				300	Note A	D	
ER 16PV	12-4 STR 12-10 SOL	Cu	1.2	1000	85	E	2(105)

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
20.550M/XX, 20.650M/XX, 20.550M/xx-P (d), 20.555M/xx-P (d), 20.650M/xx-P (d),	16-24 SOL, 18-24 STR	Cu	0.2	300	6	B,D	2(105)
21.550M/XX, 21.650M/XX, 21.550M/xx-P (d), 21.650M/xx-P (d)	16-24, SOL/STR	Cu	0.2	300	6	B, D	2(105)
20.100M/XX, 20.101M/XX, 20.105M/XX, 20.200M/XX, 20.205M/XX, 20.100M/xx-P (d), 20.200M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
20.500M/XX, 20.501M/XX, 20.600M/XX, 20.505M/XX, 20.500M/xx-P (d), 20.600M/xx-P(d)	14-20, SOL/STR	Cu	0.4	300	16	B	2(105)
20.502M/xx-P (d)	12-26, STR	Cu	0.4	300	16	B	2(105)
20.130M/XX, 20.130M/PSXX, 20.130M/PS, 20.130M/xx-P (d), 20.230M/xx-P (d)	14-20, SOL/STR	Cu	0.4	300	10	B, D	2(105), #2
	14-20, SOL/STR	Cu	0.4	150	10	C	2(105), #2
20.130M/xx-PPS (d), 20.230M/xx-PPS (d)	—	—	—	300	10	B, D	2(105), #2
	—	—	—	150	10	C	2(105), #2
21.5100M/xx-P, 21.5200M/xx-P	20-26, SOL	Cu	0.2	150	2	B,D	2(105)
	20-26, STR						
20.300M/XX, 20.300M/xx-P (d), 20.400M/xx-P (d)	12-26, SOL/STR	Cu	0.4	250	16	B	2(105)
				250	Note A	D	
20.351M/xx-P (d)	12-24, SOL/STR	Cu	0.4	250	12	B	2(105)
				250	Note A	D	
20.250M/xx-P (d)	16-26, SOL/STR	Cu	0.4	150	10	B	2(105)
20.4101M/xx-P (d), 21.4101M/xx-P (d), 20.4100M/xx-P (d) , 21.4100M/xx-P (d)	14-20, SOL/STR	Cu	2	300	10	B	2(105), 4
					Note A	D	
21.101M/XX, 21.100M/xx-P (d), 21.200M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
21.501M/XX, 21.605M/xx-P (d), 21.500M/xx-P (d), 21.505M/xx-P (d)	14-22, SOL	Cu	0.3	300	16	B	2(105)

20.110M/XX, 20.110M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
	14-22, SOL/STR	Cu	0.5	150	16	C	2(105)
20.352M/xx-P (d), 21.352M/04-P, 21.352M/06-P	14-30, SOL/STR	Cu	0.5	300	10	B,D	2(105)
20.252M/xx-P (d)	14-30, SOL/STR	Cu	0.5	300	10	B,D	2(105)
21.1550M/xx-P (d), 21.1550MF/xx-P (d)	14-24, SOL/STR	Cu	0.2	300	8	D	2(105), #2
	14-24, SOL/STR	Cu	0.2	150	8	B	2(105), #2
21.155MV/xx-P (d)	—	—	—	300	8	D	2(105), #2
	—	—	—	150	8	B	2(105), #2
21.155MH/xx-P (d)	—	—	—	300	8	D	2(105), #2
	—	—	—	150	8	B	2(105), #2
21.155MVF/xx-P (d)	—	—	—	300	8	D	2(105), #2
	—	—	—	150	8	B	2(105), #2
21.155MHF/xx-P (d)	—	—	—	300	8	D	2(105), #2
	—	—	—	150	8	B	2(105), #2
20.3303M/xx-P	14-22, SOL/STR	Cu	—	250	2	B, D	2(105)
21.105M/xx-P (d), 21.205M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
20.205M/xx-P (d), 20.105M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
20.115M/xx-P (d)	14-22, SOL/STR	Cu	0.5	300	15(#4)	B	2(105)
					Note A	D	
21.350M/2-P, 21.350M/3-P, 21.355M/2-P, 21.355M/3-P	24-12, SOL/STR	Cu	4.5	300	20	B	2(105)
				300	Note A	D	
20.356M/2-P, 20.356M/3-P, 20.357M/2-P, 20.357M/3-P	24-12, SOL/STR	Cu	4.5	300	20	B	2(105)
					Note A	D	
20.558M/xx-P (d)	16-26, SOL/STR	Cu	3.5	300	10	B	2(105)
					Note A	D	
Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.							
20.3000M/xx-P (d)	12-28, SOL/STR	Cu	—	300	15	B	2(105)
					Note A	D	

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
PM2.5(a)	22-12 SOL,STR	Cu	0.40	300	20	B, C	2(105)
				300	Note A	D	

PM4(a)	22-10 SOL	Cu	0.79	300	30	B, C	2(105)
				300	Note A	D	
PM10(a)	22-8 SOL,STR	Cu	1.75	300	45	B, C	2(105)
				300	Note A	D	
20.358M/xx (c)	12-24	Cu	0.50	300	20	B,C	2(105)
	12-24	Cu	0.50	600	Note A	D	2(105)
<p>Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.</p>							
20.1510M/xx-E, 20.1550M/xx-E, 20.1550MF/xx-E, 20.155MH/xx-E, 20.155MV/xx-E, 21.1550M/xx-E, 21.155MH/xx-E, 21.155MV/xx-E, 21.1500MF/xx-E, 21.157MVF/xx-E, 20.1500M/xx-E, 21.1500M/xx-E, 20.1500MF/xx-E, 21.1510M/xx-E, 20.1510MF/xx-E, 21.1510MF/xx-E, 21.1510MF/xx-E, 21.1550MF/xx-E, 20.156MH/xx-E, 21.156MH/xx-E, 20.156MHF/xx-E, 21.156MHF/xx-E, 20.155MHF/xx-E, 21.155MHF/xx-E, 20.157MH/xx-E, 21.157MH/xx-E, 20.157MHF/xx-E, 21.157MHF/xx-E, 20.156MV/xx-E, 21.156MV/xx-E, 20.156MVF/xx-E, 21.156MVF/xx-E, 20.155MVF/xx-E, 21.155MVF/xx-E, 20.157MV/xx-E, 21.157MV/xx-E, 20.157MVF/xx-E, 21.157MVF/xx-E (d)	16-28, Str/Sol	Cu	0.2	300	8	B	2(105),#1
					Note A	D	
21.840M/xx-E (d)	10-26, Str/Sol	Cu	0.5	300	30	B	2 (105)
					Note A	D	
21.920M/xx-E (d)	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
21.95MV/xx-E, 20.96MV/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.250M/xx-E, 21.250M/xx-E (d)	16-26 Sol/Str	Cu	0.39	300	8	B,DA	2(105)
21.800M/xx-E (d)	12-26 Sol/Str	Cu	0.41	300	20	B,DA	2(105)
20.700M/xx-E, 21.700M/xx-E (d)	12-26 Str/Sol	Cu	2	3.6	300	20	B
					Note A	D	
20.557M/xx-E, 20.558M/xx-E, 20.553M/xx-E (d)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)
					Note A	D	
21.557M/xx-E, 21.558M/xx-E, 21.553M/xx-E (d)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)
					Note A	D	
20.352M/xx-E, 20.353M/xx-E (d)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)
					Note A	D	
20.352M/xx-E, 20.353M/xx-E (d)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)
					Note A	D	
20.950M/xx-E, 21.950M/xx-E, 20.960M/xx-E, 21.960M/xx-E, 20.950MF/xx-E, 21.950MF/xx-E, 20.960MF/xx-E, 21.960MF/xx-E (d)	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
20.910M/xx-E, 21.910M/xx-E, 20.910MF/xx-E, 21.910MF/xx-E (d)	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
20.920M/xx-E, 21.920M/xx-E, 20.920MF/xx-E, 21.920MF/xx-E (d)	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
20.970M/xx-E, 21.970M/xx-E, 20.970MF/xx-E, 21.970MF/xx-E (d)	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
20.95MA/xx-E, 21.95MA/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1

20.90MH/xx-E, 21.90MH/xx-E, 20.91MH/xx-E, 21.91MH/xx-E, 20.95MH/xx-E, 21.95MH/xx-E, 20.96MH/xx-E, 21.96MH/xx-E, 20.95MHF/xx-E, 21.95MHF/xx-E, 20.96MHF/xx-E, 21.96MHF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.93MH/xx-E, 21.93MH/xx-E, 20.93MHF/xx-E, 21.93MHF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.94MH/xx-E, 21.94MH/xx-E, 20.94MHF/xx-E, 21.94MHF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.90MV/xx-E, 21.90MV/xx-E, 20.91MV/xx-E, 21.91MV/xx-E, 20.95MV/xx-E, 21.95MV/xx-E, 20.96MV/xx-E, 21.96MV/xx-E, 20.95MVVF/xx-E, 21.95MVVF/xx-E, 20.96MVVF/xx-E, 21.96MVVF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.93MV/xx-E, 21.93MV/xx-E, 20.93MVVF/xx-E, 21.93MVVF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.94MV/xx-E, 21.94MV/xx-E, 20.94MVVF/xx-E, 21.94MVVF/xx-E (d)	—	—	—	300	15	B,DA	2(105),#1
20.843M/xx-E (d)	6-20, Str/Sol	Cu	1.4	300	52	B, C	2 (105)
				600	Note A	D	
20.130M/xx-E, 20.230M/xx-E (d)	—	—	—	300	10	B	2 (105), #1
					Note A	D	
20.130M/xx-E, 20.230M/xx-E (d)	16-28, Str/Sol	Cu	0.4	300	10	B	2 (105), #1
					Note A	D	
21.840M/xx-E (d)	10-26, Str/Sol	Cu	0.5	300	30	B	2 (105)
					Note A	D	
Plug-in blocks							
20.962M/xx-E	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
21.962M/xx-E	28-14, Str/Sol	Cu	0.51	300	15	B,DA	2(105),#1
Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or the maximum ampere rating, whichever is less.							
21.843M/xx-P (e)	22-6, SOL/STR	Cu	1.1	600	36	B, C	2(105)
				600	Note A	D	
Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.							

Cat. No.	Wire Range	Wire Type	FW	TQ Lb In.	V	A	UG	CA
PF 2.5	22-12	Cu	2	—	600	20	B,C	2(105),4
PFPE 2.5P	22-12	Cu	2	—	—	—	B,C	2(105),4
PF 4	22-10	Cu	2	—	600	30	B,C	2(105),4
PFPE 4P	22-10	Cu	2	—	—	—	B,C	2(105),4
PF 6	20-8	Cu	2	—	600	35	B,C,D(1)	2(105),4
PFPE 6P	20-8	Cu	2	—	600	—	B,C,D(1)	2(105),4
PFD 4	22-10	Cu	2	—	300	30	B, C	2(105), 4
PFD 2,5E	22-12	Cu	2	—	600	20	B, C, D	2(105), 4
PFD 2,5PE	22-12	Cu	2	—	600	—	B, C, D	2(105), 4
PFTD 2,5	22-12	Cu	2	—	300	16	B, C, D	2(105), 4
PFTD 2,54	12	Cu	2	—	300	10	B, C, D	2(105), 4
PFD 2.5C	22-12 SOL 22 STR	Cu	2	—	600	20	B, C, D	2(105), 4
PFD 2,5CPE	22-12 SOL 22 STR	Cu	2	—	600	—	B, C, D	2(105), 4
PFT 3S	22-12 SOL 22 STR	Cu	2	—	300	20	B, C, D	2(105), 4

PFD 4E	22-10	Cu	2	—	600	30	B, C, D	2(105), 4
PFT	22-14	Cu	2	—	300	15	B, C, D	2(105), 4
PFM 2,5	22-12	Cu	2	—	600	20	B, C, D	2(105), 4
PFPEM 2,5	22-12	Cu	2	—	600	—	B, C, D	2(105), 4
20.350M/xx-E (d)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)	14-30, Str/Sol
21.350M/xx-E (d)	14-30, Str/Sol	Cu	2	3.6	300	15	B	2(105), 4
					300	Note A	D	
20.3303M/xx-E (d)	18-22 Str	Cu	2	—	300	5	B,DA	2(105), 4
20.3304M/xx-E (d)	18-22 Str	Cu	2	—	300	5	B,DA	2(105), 4
20.3301M/xx-E (d)	28-20, str/sol	Cu	—	300	4	B	2(105)	
					Note A	D		
20.3302M/xx-E (d)	28-20, str/sol	Cu	—	300	4	B	2(105)	
					Note A	D		

Note: A - These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or 5 A at 301-600 V, or the maximum ampere rating, whichever is less.

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
21.890M/xx-E (h)	20-6, str/sol	Cu	1.8	600	65	B, C	2(105)
					Note A	D	
20.7000M/(f)	20-4, str/sol	Cu	—	300	70	B, DA	2(120)
20.952M/xx-T (h)	24-14, str/sol	Cu	0.4	300	15	B	2(115), 4

Terminal blocks							
20.5300M/xx-E (d)	14-24, Str/Sol	Cu	—	300	10	B	2 (105), 4
21.5300M/xx-E (d)	14-24, Str/Sol	Cu	—	300	10	B	2 (105), 4
21.5400M/xx-E (h)	14-24, Str/Sol	Cu	—	300	10	B	2 (105)
					Note A	D	
20.5401M/xx-E (h)	26-16, str/sol	Cu	—	300	10	B	2 (105)
PF 10	22-6	Cu	—	600	55	B, C, D	2(105), 4
PF 16	4-20	Cu	—	600	80	B, C	2(105)
PFD 2,5	22-12	Cu	—	300	20	B, C	2(105), 4
				600		D	
PFD 2,5V	22-12	Cu	—	300	20	B, C	2(105), 4
				600		D	
PFD 6C	8-20	Cu	—	600	48	B, C	2(105)
PFD 6E	8-20	Cu	—	600	48	B, C	2(105)
PFF 3	22-10	Cu	—	150	10	C	2(105)
				300		B, D	
PFF4	22-10	Cu	—	150	10	C	2(105)
				300		B, D	
20.6002M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
21.6002M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
20.6003M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
21.6003M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
20.6004M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
21.6004M/xx-E (h)	12-28 Sol	Cu	—	300	10	B,DA	2(105)
21.4102M/xx-E (h)	22-18, str/sol	Cu	—	300	5	B	2(120)
					Note A	D	

20.4101M/xx-E (h)	22-18, str/sol	Cu	—	300	5	B	2(120)
					Note A	D	
20.702M/xx-E (h)	12-26 Str/Sol	Cu	2	3.6	300	20	B
21.702M/xx-E (h)	12-26 Str/Sol	Cu	2	3.6	300	20	B
20.103M/xx-E (h)	14-26, Str/Sol	Cu	2	3.6	300	15	B
20.7031M/xx-E (h)	18-4, str/sol	Cu	—	600	66	B,C	2(125)
					Note A	D	
20.7021M/xx-E(h)	18-4, str/sol	Cu	—	600	66	B, C	2(125)

Terminal blocks

Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
21.843M-xx/E (h)	6-20, str/sol	Cu	1.4	300	52	B, C	2 (105)
21.352M-xx/E (h)	14-30, str/sol	Cu	0.4	300	15	B	2 (105)
21.353M-xx/E (h)	14-30, str/sol	Cu	0.4	300	15	B	2 (105)
23.843M/xx-E (b)	12-22 Sol/Str	Cu	2	300	20	B, D	2 (105)
20.753M/xx-E (h)	14-30, Str/Sol	Cu	0.4	300	15	B	2(105)
					Note A	D	

Headers							
20.95MHT/xx-E (h)	28-12, Str/Sol	Cu	0.51	300	15	B,D ^A	2(105),#1
21.95MHT/xx-E (h)	28-12, Str/Sol	Cu	0.51	300	15	B,D ^A	2(105),#1



Cat. No.	Wire Range	Wire Type	TQ N-M	V	A	UG	CA
ER 70PV	6-2/0	Cu	10	1000	175	E	2(105)
ER70 GPV	6-2/0	Cu	10	1000	175	E	2(105)

- (a) Followed by 2 - 7 alpha-numeric digits.
- (b) The following two wires combinations are allowed for this model of terminal blocks: 18 awg+18 awg, 20 awg+20 awg, 22 awg+ 22 awg, 18 awg+ 20 awg, 20 awg+22 awg.
- (c) where xx indicates 02 through 12.
- (d) where xx indicates 02 through 24.
- (e) where xx is followed by -2 through -3.
- (f) (b) Followed by one or two digit number, may be followed by P, may be followed by two numbers or one number and one letter, maybe followed by letters to represent 00-9999999999, followed by nil for A(H), B for B(H) C for C(H) up to Z for Z(H).
- (g) Where XX is either 02 or 03.
- (h) - Where xx indicates the number of poles.
- (+) xx indicates followed by 02 through 20.

Note A: These limited ratings are applicable to a terminal block for use in or with industrial control equipment whereby the load on any single circuit of the terminal block does not exceed 15 A at 51-150 V, 10 A at 151-300 V, or the maximum ampere rating, whichever is less.

#1 The terminal blocks as tabulated below consist of two halves with plug consisting of the Pressure Wire Connector Type and header consisting of the Soldering Post Type terminals. These devices have not been evaluated to make or break the flow of current. These devices are not evaluated for use with any other mating connectors.

Plug-in Block Series No.	Mating Header Series No.
20.962M, 21.962M	20.93MV, 21.93MV, 20.93MH, 21.93MH, 20.94MV, 21.94MV, 20.94MH, 21.94MH

Marking: Company name or Trademark  and Recognized Component Mark for Canada, , on the product. Catalog designation, maximum voltage, wire range, and ampere rating appear on the device or, in or on the carton.

Last Updated on 2019-08-26

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

Reprinted from the Online Certifications Directory with permission from UL