

**EPBU2.E316757****Direct-plug-in and Cord-connected Class 2 Power Units - Component**[Page Bottom](#)**Direct-plug-in and Cord-connected Class 2 Power Units - Component**[See General Information for Direct-plug-in and Cord-connected Class 2 Power Units - Component](#)**IMO PRECISION CONTROLS LTD**

E316757

1000 N Circular Rd
Staples Corner
London, NW2 7JP UNITED KINGDOM

Class 2 power supplies, Model(s) DPS-1-005-05, DPS-1-005-05B, DPS-1-005-12, DPS-1-005-12B, DPS-1-005-15, DPS-1-005-15B, DPS-1-005-24, DPS-1-005-24B, DPS-1-010-05, DPS-1-010-05B, DPS-1-010-12, DPS-1-010-12B, DPS-1-010-15, DPS-1-010-15B, DPS-1-010-24, DPS-1-010-24B, DPS-1-018-05, DPS-1-018-05B, DPS-1-018-12, DPS-1-018-12B, DPS-1-018-15, DPS-1-018-15B, DPS-1-018-24, DPS-1-018-24B, MPS-1-015-5, MPS-1-024-12, MPS-1-024-15, MPS-1-024-24

Class 2 power units, Model(s) DPS-1-030-12, DPS-1-030-12B, DPS-1-030-24, DPS-1-030-24B, DPS-1-030-48, DPS-1-030-48B, DPS-1-060-24, DPS-1-060-24B, DPS-1-060-48, DPS-1-060-48B, DPS-1-100-24L, DPS-1-120-24BL, DPS-1-120-24L, MPS-1-007-5, MPS-1-010-12, MPS-1-010-15, MPS-1-010-24, MPS-1-022-5, MPS-1-033-12, MPS-1-036-15, MPS-1-036-24, MPS-1-054-12, MPS-1-060-15, MPS-1-060-24

Note - Where z may be any alphanumeric character or blank.

Marking: Company name and model designation.

Last Updated on 2015-11-30

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

Reprinted from the Online Certifications Directory with permission from UL

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".



QQGQ2.E316758 Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

Page Bottom

Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

See General Information for Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

IMO PRECISION CONTROLS LTD

E316758

The Interchange Frobisher Way
Hatfield, AL10 9TG UNITED KINGDOM

Model No.	Rated Input			Max Output				SP	EP	FC	GC
	Volts	Hz	SC	V	A	VA	OC				
Component power supply.											
BPS-1-100-12 DC[*r]	100-240ac	50/60	0	12dc	8	96	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-120-24 DC[*r]	100-240ac	50/60	0	24dc	5	120	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-120-48 DC[*r]	100-240ac	50/60	0	48dc	2.5	120	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-15-12 DC[*r]	100-240ac	50/60	0	12dc	1.2	14.4	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-15-24 DC[*r]	100-240ac	50/60	0	24dc	0.65	15.6	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-180-24 DC[*r]	100-240ac	50/60	0	24dc	7.5	180	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-180-48 DC[*r]	100-240ac	50/60	0	48dc	3.8	182.4	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-240-24 DC[*r]	100-240ac	50/60	0	24dc	10	240	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-240-48 DC[*r]	100-240ac	50/60	0	48dc	5	240	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-30-12 DC[*r]	100-240ac	50/60	0	12dc	2.5	30	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-30-24 DC[*r]	100-240ac	50/60	0	24dc	1.3	31.2	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-30-5 DC[*r]	100-240ac	50/60	0	5dc	5	25	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-50-12 DC[*r]	100-240ac	50/60	0	12dc	4.2	50.4	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-50-24 DC[*r]	100-240ac	50/60	0	24dc	2.2	52.8	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-50-48 DC[*r]	100-240ac	50/60	0	48dc	1.1	52.8	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-60-12 DC[*r]	100-240ac	50/60	0	12dc	5	60	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-70-24 DC[*r]	100-240ac	50/60	0	24dc	3	72	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
BPS-1-70-48 DC[*r]	100-240ac	50/60	0	48dc	1.5	72	3	60950-1, 2nd Ed+AM1+AM2	20	0	1
DPS -1-480-24	115/230ac	47-63	0	24.07dc	27.3	567.1	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS -1-480-48	115/230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1, 2nd Ed	20B	0	1

								+ AM1			
DPS -1-480-48B	115/230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-005-05[*r]	100-240ac	47-63	0	5dc	-	5	3	60950-1	20B	0	1
DPS-1-005-05B[*r]	100-240ac	47-63	0	5dc	-	5	3	60950-1, 2nd	20B	0	1
DPS-1-005-12[*r]	100-240ac	47-63	0	12dc	-	5	3	60950-1	20B	0	1
DPS-1-005-12B[*r]	100-240ac	47-63	0	12dc	-	5	3	60950-1, 2nd	20B	0	1
DPS-1-005-15[*r]	100-240ac	47-63	0	15dc	-	5	3	60950-1	20B	0	1
DPS-1-005-15B[*r]	100-240ac	47-63	0	15dc	-	5	3	60950-1, 2nd	20B	0	1
DPS-1-005-24[*r]	100-240ac	47-63	0	24dc	-	5	3	60950-1	20B	0	1
DPS-1-005-24B[*r]	100-240ac	47-63	0	24dc	-	5	3	60950-1, 2nd	20B	0	1
DPS-1-010-05[*r]	100-240ac	47-63	0	5dc	-	10	3	60950-1	20B	0	1
DPS-1-010-05B[*r]	100-240ac	47-63	0	5dc	-	10	3	60950-1, 2nd	20B	0	1
DPS-1-010-12[*r]	100-240ac	47-63	0	12dc	-	10	3	60950-1	20B	0	1
DPS-1-010-12B[*r]	100-240ac	47-63	0	12dc	-	10	3	60950-1, 2nd	20B	0	1
DPS-1-010-15[*r]	100-240ac	47-63	0	15dc	-	10	3	60950-1	20B	1	0
DPS-1-010-15B[*r]	100-240ac	47-63	0	15dc	-	10	3	60950-1, 2nd	20B	1	0
DPS-1-010-24[*r]	100-240ac	47-63	0	24dc	-	10	3	60950-1	20B	1	0
DPS-1-010-24B[*r]	100-240ac	47-63	0	24dc	-	10	3	60950-1, 2nd	20B	1	0
DPS-1-018-05[*r]	100-240ac	47-63	0	5dc	-	15	3	60950-1	20B	1	0
DPS-1-018-05B[*r]	100-240ac	47-63	0	5dc	-	15	3	60950-1, 2nd	20B	1	0
DPS-1-018-12[*r]	100-240ac	47-63	0	12dc	-	18	3	60950-1	20B	1	0
DPS-1-018-12B[*r]	100-240ac	47-63	0	12dc	-	18	3	60950-1, 2nd	20B	1	0
DPS-1-018-15[*r]	100-240ac	47-63	0	15dc	-	18	3	60950-1	20B	1	0
DPS-1-018-15B[*r]	100-240ac	47-63	0	15dc	-	18	3	60950-1, 2nd	20B	1	0
DPS-1-018-24[*r]	100-240ac	47-63	0	24dc	-	18	3	60950-1	20B	1	0
DPS-1-018-24B[*r]	100-240ac	47-63	0	24dc	-	18	3	60950-1, 2nd	20B	1	0
DPS-1-030-05	100-240ac	47-63	0	5.87dc	7.9	41.38	3	60950-1	20B	0	1
DPS-1-030-05B	100-240ac	47-63	0	5	-	30	3	60950-1, 2nd	20B	0	1
DPS-1-030-12	100-240ac	47-63	0	14.96dc	4	45.88	3	60950-1	20B	0	1
DPS-1-030-12B	100-240ac	47-63	0	12	-	30	3	60950-1, 2nd	20B	0	1
DPS-1-030-24	120-240ac	47-63	0	24dc	-	30	3	60950-1	20B	0	1
DPS-1-030-24B	100-240ac	47-63	0	24	-	30	3	60950-1, 2nd	20B	0	1
DPS-1-030-48	100-240ac	47-63	0	56.87dc	0.93	42	3	60950-1	20B	0	1

DPS-1-030-48B	100-240ac	47-63	0	48	-	30	3	60950-1, 2nd	20B	0	1
DPS-1-060-05	100-240ac	47-63	0	5.73dc	11.4	57.2	3	60950-1	20B	0	1
DPS-1-060-05B	100-240ac	47-63	0	5	-	60	3	60950-1, 2nd	20B	0	1
DPS-1-060-12	100-240ac	47-63	0	14.76dc	7	87	3	60950-1	20B	0	1
DPS-1-060-12B	100-240ac	47-63	0	12	-	60	3	60950-1, 2nd	20B	0	1
DPS-1-060-24	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
DPS-1-060-24B	100-240ac	47-63	0	24	-	60	3	60950-1, 2nd	20B	0	1
DPS-1-060-48	100-240ac	47-63	0	28.5dc	3.48	91.45	3	60950-1	20B	0	1
DPS-1-060-48B	100-240ac	47-63	0	48	-	60	3	60950-1, 2nd	20B	0	1
DPS-1-100-12	100-240ac	47-63	0	12.167	15.94	113.88	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-100-24[*r]	100-240ac	47-63	0	24	-	100	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-100-24L[*r]	100-240ac	47-63	0	24	-	92	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-100-48	100-240ac	47-63	0	48.13	5.5	134.56	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-120-12, DPS-1-120-12B											
	115/220/230ac	47-63	0	12.02	14	124.68	3	60950-1	20B	0	1
DPS-1-120-24, DPS-1-120-24B											
	115/220/230ac	47-63	0	24.07	7.6	131.7	3	60950-1	20B	0	1
DPS-1-120-24BL	115/220/230ac	47-63	0	24.07	7.6	131.7	3	60950-1	20B	0	1
DPS-1-120-24L	115/220/230ac	47-63	0	24.07	7.6	131.7	3	60950-1	20B	0	1
DPS-1-120-48, DPS-1-120-48B											
	115/220/230ac	47-63	0	47.89	3.8	150.08	3	60950-1	20B	0	1
DPS-1-240-24	115/230ac	47-63	0	24dc	14.5	308.1	3	60950-1	20B	0	1
DPS-1-240-24B	115/230ac	47-63	0	24dc	14.5	308.1	3	60950-1	20B	0	1
DPS-1-240-48	115/230ac	47-63	0	47.9dc	8	286.7	3	60950-1	20B	0	1
DPS-1-240-48B	115/230ac	47-63	0	47.9dc	8	286.7	3	60950-1	20B	0	1
DPS-1-300-24DC	115/230 or 115/220/230ac	47-63	0	24.12dc	19.6	395	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-300-48DC	115/230 or 115/220/230ac	47-63	0	49.15dc	11.8	349.5	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-1-480-24	115/230ac	47-63	0	24.07dc	27.3	567.1	3	60950-1	20B	0	0
DPS-1-480-24B	115-230ac	47-63	0	24.07dc	27.3	567.1	3	60950-1	20B	0	1
DPS-1-480-48	115/230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1	20B	0	0
DPS-1-480-48B	115-230ac	47-63	0	48.05dc	13.5	583.9	3	60950-1	20B	0	1
DPS-3-120-12	3PH 400-500ac	47/63	0	12.08dc	14.8	142.76	3	60950-1, 2nd Ed + AM1	20B	0	1
DPS-3-120-24	3PH 400-500Vac	47-63	0	24.08dc	6.95	152.32	-	60950-1, 2nd Ed + AM1	20B	0	1
DPS-3-240-24	3PH 400-500Vac	47-63	0	24.1dc	13.7	289.92	3	60950-1, 2nd	20B	0	1
DPS-3-240-48	3PH 400-500Vac	47-63	0	48.03dc	6.32	279.93	3	60950-1, 2nd	20B	0	1
DPS-3-480-24	3PH 400-500ac	47-63	0	24.1dc	29.6	513	3	60950-1, 2nd	20B	1	0
DPS-3-480-48	3PH 400-500ac	47-63	0	48.2dc	19.7	498	3	60950-1, 2nd	20B	1	0
DPS-3-960-24	3PH 400-500Vac	47-63	0	24.1dc	44.5	1038	3	60950-1, 2nd	20B	0	1
DPS-3-960-24L	3PH 400-500Vac	47-63	0	24.1dc	44.5	1038	3	60950-1, 2nd	20B	0	1
DPS-3-960-48	3PH 400-500Vac	47-63	0	48.1dc	27.5	1176	3	60950-1, 2nd	20B	0	1
MPS-1-007-	100-240ac	47-63	0	5	-	7.5	3	60950-1, 2nd	20B	0	2

5[*r]												
MPS-1-010-12[*r]	100-240ac	47-63	0	12	-	10	3	60950-1, 2nd	20B	0	2	
MPS-1-010-15[*r]	100-240ac	47-63	0	15	-	10	3	60950-1, 2nd	20B	0	2	
MPS-1-010-24[*r]	100-240ac	47-63	0	24	-	10	3	60950-1, 2nd	20B	0	2	
MPS-1-015-5	100-240ac	47-63	0	5.1	4.3	21.3	3	60950-1, 2nd	20B	0	2	
MPS-1-022-5[*r]	100-240ac	47-63	0	5	-	22.5	3	60950-1, 2nd	20B	0	2	
MPS-1-024-12[*r]	100-240ac	47-63	0	12	2	-	3	60950-1, 2nd	20B	0	2	
MPS-1-024-15[*r]	100-240ac	47-63	0	15	1.6	-	3	60950-1, 2nd	20B	0	2	
MPS-1-024-24	100-240ac	47-63	0	24.0	1.3	31.2	3	60950-1, 2nd	20B	0	2	
MPS-1-033-12[*r]	100-240ac	47-63	0	12	-	33	3	60950-1, 2nd	20B	0	2	
MPS-1-035-5[*r]	100-240ac	47-63	0	5	-	35	3	60950-1, 2nd	20B	0	2	
MPS-1-036-15[*r]	100-240ac	47-63	0	15	-	36	3	60950-1, 2nd	20B	0	2	
MPS-1-036-24[*r]	100-240ac	47-63	0	24	-	36	3	60950-1, 2nd	20B	0	2	
MPS-1-054-12[*r]	100-240ac	47-63	0	12	-	54	3	60950-1, 2nd	20B	0	2	
MPS-1-060-15[*r]	100-240ac	47-63	0	15	-	60	3	60950-1, 2nd	20B	0	2	
MPS-1-060-24[*r]	100-240ac	47-63	0	24	-	60	3	60950-1, 2nd	20B	0	2	
MPS-1-060-5[*r]	100-240ac	47-63	0	5	-	60	3	60950-1, 2nd	20B	0	2	
MPS-1-072-12[*r]	100-240ac	47-63	0	12	-	72	3	60950-1, 2nd	20B	0	2	
MPS-1-075-15[*r]	100-240ac	47-63	0	15	-	75	3	60950-1, 2nd	20B	0	2	
MPS-1-100-24[*r]	100-240ac	47-63	0	24	-	91	3	60950-1, 2nd	20B	0	2	

[*r] - Output values are rated.

C - = RoHS (C5=RoHS5, C6=RoHS6 or blank)

L - =Pin length(L1: 2.8, L2: 4.57, L3: 5.8, L4: 6.35 or blank)

T - = Temperature range(T1, T2, T3? represents different temperature range)

Y - Y=05, 12, 15 or 24

Marking: Company name and model designation on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2018-01-16

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

Reprinted from the Online Certifications Directory with permission from UL

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".



QQPX2.E477091 Power Supplies for Use in Hazardous Locations - Component

[Page Bottom](#)

Power Supplies for Use in Hazardous Locations - Component

[See General Information for Power Supplies for Use in Hazardous Locations - Component](#)

IMO PRECISION CONTROLS LTD

E477091

1000 N Circular Rd
Staples Corner
London, NW2 7JP UNITED KINGDOM

Class I, Division 2, Groups A, B, C and D, Model(s) DPS -1-480-24, DPS -1-480-24B, DPS -1-480-48, DPS -1-480-48B, DPS-1-120-12, DPS-1-120-12B, DPS-1-120-24, DPS-1-120-24B, DPS-1-120-24BL, DPS-1-120-24L, DPS-1-120-48, DPS-1-120-48B, DPS-1-240-24, DPS-1-240-24B, DPS-1-240-48, DPS-1-240-48B, DPS-1-300-24, DPS-1-300-24B, DPS-1-300-24DC, DPS-1-300-48, DPS-1-300-48B, DPS-1-300-48DC, DPS-3-120-12, DPS-3-120-24, DPS-3-240-24, DPS-3-240-48, DPS-3-480-24, DPS-3-480-48, DPS-3-960-24, DPS-3-960-24L, DPS-3-960-48, MPS-1-007-5, MPS-1-010-12, MPS-1-010-15, MPS-1-010-24, MPS-1-033-12, MPS-1-035-5, MPS-1-036-15, MPS-1-036-24, MPS-1-054-12, MPS-1-060-15, MPS-1-060-24, MPS-1-060-5, MPS-1-072-12, MPS-1-075-15, MPS-1-100-24

Class I, Division 2, Groups A, B, C and D (switching power supplies), Model(s) DPS-1-100-12, DPS-1-100-24, DPS-1-100-24L, DPS-1-100-48, MPS-1-015-5, MPS-1-022-5, MPS-1-024-12, MPS-1-024-15, MPS-1-024-24

Marking: Company name and model designation.

[Last Updated](#) on 2016-05-18

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

Reprinted from the Online Certifications Directory with permission from UL

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".